



Firma: Desk
Adresa: Čika Ljubina 20
Telefon: +381113287160
Fax: +381113292140
PIB: 101520010
E-mail: plato@desk.rs

LAN Router TP-LINK TL-WR841N Wireless

Šifra:
Kategorija proizvoda: Ruteri i ekstenderi
Proizvođač: TP-Link

Cena: **2.849,00** rsd.

LAN Router TP-LINK TL-WR841N Wireless

HARDWARE FEATURES

Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Button	Quick Setup Security Button Reset Button
External Power Supply	9VDC / 0.6A
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Antenna	2*5dBi Fixed Omni Directional Antenna
Dimensions (W x D x H)	7.6 x 5.1 x 1.3 in.(192 x 130 x 33 mm)

WIRELESS FEATURES

Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
EIRP	<20dBm(EIRP)
Reception Sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK

SOFTWARE FEATURES

WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
DHCP	Server, Client, DHCP Client List, Address Reservation
Quality of Service	WMM, Bandwidth Control
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding

SOFTWARE FEATURES

Management	Access Control Local Management Remote Management
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	Wireless N Router TL-WR841N Power supply unit Resource CD Quick Installation Guide
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0~40°C (32~104°F) Storage Temperature: -40~70°C (-40~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing