



Firma: Desk
Adresa: Čika Ljubina 20
Telefon: +381113287160
Fax: +381113292140
PIB: 101520010
E-mail: plato@desk.rs

LAN Switch TP-LINK TL-SG1005P 101001000
5port (4 PoE)

Šifra:
Kategorija proizvoda: Switch uređaji
Proizvođač: TP-Link

Cena: **5.365,00** rsd.

LAN Switch TP-LINK TL-SG1005P 101001000 5port (4 PoE)

HARDWARE FEATURES

| | |
|---------------------------------|---|
| Interface | <ul style="list-style-type: none">• 5× 10/100/1000Mbps RJ45 Ports• AUTO Negotiation• AUTO MDI/MDIX |
| Network Media | <ul style="list-style-type: none">• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)• EIA/TIA-568 100Ω STP (maximum 100m)• 100BASE-TX: UTP category 5, 5e cable (maximum 100m)• EIA/TIA-568 100Ω STP (maximum 100m)• 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)• EIA/TIA-568 100Ω STP (maximum 100m) |
| Fan Quantity | Fanless |
| External Power Supply | External Power Adapter (Output: 53.5 VDC / 1.31 A) |
| Packet Forwarding Rate | 7.44 Mpps |
| PoE Ports (RJ45) | <ul style="list-style-type: none">• Standard: 802.3af/at compliant• PoE Ports: Ports 1-4• Power Supply: 65 W |
| Mac Address Table | 2K |
| Jumbo Frame | 16 KB |
| Switching Capacity | 10 Gbps |
| Dimensions (W x D x H) | 3.9×3.9×1.0 in (99.8×98×25 mm) |
| Max Power Consumption | <ul style="list-style-type: none">• 4.29 W (220/50 Hz. no PD connected)• 74.24 W (220/50 Hz. with 65 W PD connected) |
| Max Heat Dissipation | <ul style="list-style-type: none">• 14.63 BTU/h (no PD connected)• 253.16 BTU/h (with 65 W PD connected) |

SOFTWARE FEATURES

| | |
|--------------------------|---|
| Advanced Features | <ul style="list-style-type: none">• Compatible With IEEE 802.3af/at Compliant PDs• Mac Address Auto-Learning And Auto-Aging• IEEE 802.3x Flow Control• 802.1p/DSCP QoS• IGMP Snooping |
| Transfer Method | Store-And-Forward |

OTHERS

| | |
|-------------------------|---|
| Certification | FCC, CE, RoHS |
| Package Contents | <ul style="list-style-type: none">• TL-SG1005P• Power Adapter• Installation Guide |

OTHERS**Environment**

- Operating Temperature: 0-40 ° (32-104 °);
- Storage Temperature: -40-70 ° (-40-158 °)
- Operating Humidity: 10-90% RH non-condensing
- Storage Humidity: 5-90% RH non-condensing