

## MB s1700 ASRock H610M-H2M.2 D4

---

Šifra:

Kategorija proizvoda: Matične ploče za Intel socket

Proizvođač: AS Rock

Cena: **7.161,00** rsd.

## MB s1700 ASRock H610M-H2M.2 D4

Unique Feature

### Rock-Solid Durability

- 3+1+1 Power Phase

### EZ Update

- ASRock Auto Driver Installer

CPU

- Supports 14<sup>th</sup>, 13<sup>th</sup> & 12<sup>th</sup> Gen Intel® Core™ Processors (LGA1700)
- Supports Intel® Hybrid Technology
- Supports Intel® Turbo Boost Max 3.0 Technology

Chipset

- Intel® H610

Memory

- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- Supports DDR4 non-ECC, un-buffered memory up to 3200
- Supports ECC UDIMM memory modules (operate in non-ECC mode)
- Max. capacity of system memory: 64GB
- Supports Intel® Extreme Memory Profile (XMP) 2.0

BIOS

- 128Mb AMI UEFI Legal BIOS with GUI support

Graphics

- Intel® Xe Graphics Architecture (Gen 12)
- 2 x HDMI 2.1 TMDS Compatible, support HDCP 2.3 and max. resolution up to 4K 60Hz

\* Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.

Audio

- 7.1 CH HD Audio (Realtek ALC897 Audio Codec)

LAN

- Gigabit LAN 10/100/1000 Mb/s
- Realtek 8111H

Slots

- 1 x PCIe 4.0 x16 Slot (PCIE1), supports x16 mode\*

Chipset:

- 1 x PCIe 3.0 x1 Slot (PCIE2)\*

\* Supports NVMe SSD as boot disks

Storage

Chipset:

- 1 x Ultra M.2 Socket (M2\_1, Key M), supports type 2242/2260/2280 PCIe Gen3x4 (32 Gb/s) mode\*

4 x SATA3 6.0 Gb/s Connectors

\* Supports NVMe SSD as boot disks

USB

- 4 x USB 3.2 Gen1 Type-A (2 Rear, 2 Front)

- 6 x USB 2.0 (4 Rear, 2 Front)

\* All USB ports support ESD Protection

Connector

- 1 x SPI TPM Header

- 1 x Chassis Intrusion and Speaker Header

- 1 x CPU Fan Connector (4-pin)\*

- 1 x Chassis/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)\*\*

- 1 x 24 pin ATX Power Connector

- 1 x 8 pin 12V Power Connector

- 1 x Front Panel Audio Connector

- 1 x USB 2.0 Header (Supports 2 USB 2.0 ports)

- 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)

\* CPU\_FAN1 supports the fan power up to 1A (12W).

\*\* CHA\_FAN1/WP supports the fan power up to 2A (24W).

CHA\_FAN1/WP can auto detect if 3-pin or 4-pin fan is in use.

Rear Panel I/O

- 1 x PS/2 Mouse/Keyboard Port

- 2 x HDMI Ports

- 2 x USB 3.2 Gen1 Type-A Ports

- 4 x USB 2.0 Ports

- 1 x RJ-45 LAN Port

- HD Audio Jacks: Line in / Front Speaker / Microphone

Software and UEFI

**Software**

- ASRock Motherboard Utility (A-Tuning)

**UEFI**

- ASRock EZ Mode

- ASRock Full HD UEFI

- ASRock My Favorites in UEFI

- ASRock Auto Driver Installer

- ASRock Instant Flash

\*These utilities can be downloaded from ASRock Live Update & APP Shop.

Accessories

- 1 x I/O Shield

- 2 x SATA Data Cables

- 1 x Screw for M.2 Socket

Form Factor

- Micro ATX Form Factor: 8.66-in x 7.6-in, 22.0 cm x 19.3 cm

OS

- Microsoft Windows® 10 64-bit / 11 64-bit

Certifications

- FCC, CE

- ErP/EuP ready (ErP/EuP ready power supply is required)

Link proizvođača: <https://www.asrock.com/MB/Intel/H610M-H2M.2/index.asp#Specification>