Firma: Desk
Adresa: Čika Ljubina 20
Telefon: +381113287160
Fax: +381113292140
PIB: 101520010
E-mail: plato@desk.rs

MB s1700 ASRock H610M-H2M.2 D4

Cena: 8.526,00 rsd.

Šifra:
Kategorija prozivoda: Matične ploče za Intel socket
Proizvođač: AS Rock



Unique Feature
Rock-Solid Durability
- 3+1+1 Power Phase
EZ Update
- ASRock Auto Driver Installer
CPU
- Supports 14th, 13th & 12th Gen Intel® Core™ Processors (LGA1700)
- Supports Intel® Hybrid Technology
- Supports Intel® Turbo Boost Max 3.0 Technology
Chipset
- Intel® H610
Memory
- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- Supports DDR4 non-ECC, un-buffered memory up to 3200
- Supports ECC UDIMM memory modules (operate in non-ECC mode)
- Max. capacity of system memory: 64GB
- Supports Intel® Extreme Memory Profile (XMP) 2.0
BIOS
- 128Mb AMI UEFI Legal BIOS with GUI support
Graphics
- Intel® Xe Graphics Architecture (Gen 12)
- 2 x HDMI 2.1 TMDS Compatible, support HDCP 2.3 and max. resolution up to 4K 60Hz

* Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.
Audio
- 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
LAN
- Gigabit LAN 10/100/1000 Mb/s
- Realtek 8111H
Slots
CPU:
- 1 x PCIe 4.0 x16 Slot (PCIE1), supports x16 mode*
Chipset:
- 1 x PCIe 3.0 x1 Slot (PCIE2)*

* Supports NVMe SSD as boot disks
Storage
Chipset:
- 1 x Ultra M.2 Socket (M2_1, Key M), supports type 2242/2260/2280 PCIe Gen3x4 (32 Gb/s) mode*
- 4 x SATA3 6.0 Gb/s Connectors

* Supports NVMe SSD as boot disks
USB

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.

- 1 x SPI TPM Header
- 1 x Chassis Intrusion and Speaker Header
- 1 x CPU Fan Connector (4-pin)*
- 1 x Chassis/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)**
- 1 x 24 pin ATX Power Connector
- 1 x 8 pin 12V Power Connector
- 1 x Front Panel Audio Connector
- 1 x USB 2.0 Header (Supports 2 USB 2.0 ports)
- 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)

* CPU_FAN1 supports the fan power up to 1A (12W).
** CHA_FAN1/WP supports the fan power up to 2A (24W).
CHA_FAN1/WP can auto detect if 3-pin or 4-pin fan is in use.
Rear Panel I/O
- 1 x PS/2 Mouse/Keyboard Port
- 2 x HDMI Ports
- 2 x USB 3.2 Gen1 Type-A Ports
- 4 x USB 2.0 Ports
- 1 x RJ-45 LAN Port
- HD Audio Jacks: Line in / Front Speaker / Microphone
Software and UEFI
Software
- ASRock Motherboard Utility (A-Tuning)
UEFI
- ASRock EZ Mode
- ASRock Full HD UEFI
- ASRock My Favorites in UEFI
- ASRock Auto Driver Installer
- ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.
Accessories
- 1 x I/O Shield
- 2 x SATA Data Cables
- 1 x Screw for M.2 Socket
Form Factor
- Micro ATX Form Factor: 8.66-in x 7.6-in, 22.0 cm x 19.3 cm
OS
- Microsoft Windows® 10 64-bit / 11 64-bit
Certifications
- FCC, CE
- ErP/EuP ready (ErP/EuP ready power supply is required)

Link proizvodjaca: https://www.asrock.com/MB/Intel/H610M-H2M.2/index.asp#Specification