

Wireless TP-Link Archer C20

Šifra: ARCHERC20

Kategorija proizvoda: Ruteri i ekstenderi

Proizvođač: TP-Link

Cena: **4.199,00** rsd.



Standards Wi-Fi 5

IEEE 802.11ac/n/a 5 GHz

IEEE 802.11n/b/g 2.4 GHz

WiFi Speeds AC750

5 GHz: 433 Mbps (802.11ac)

2.4 GHz: 300 Mbps (802.11n)

WiFi Range 2 Bedroom Houses

3x Fixed Antennas

Multiple antennas form a signal-boosting array to cover more directions and large areas

WiFi Capacity Medium

Dual-Band

Allocate devices to different bands for optimal performance

Working Modes Router Mode

Access Point Mode

Range Extender Mode

HARDWARE

Processor Single-Core CPU

Ethernet Ports 1x 10/100 Mbps WAN Port

4x 10/100 Mbps LAN Ports

Buttons WPS/Wi-Fi Button

Power On/Off Button

Reset Button

Power 9 V □ 0.6 A

SECURITY
WiFi Encryption WEP
WPA
WPA2
WPA/WPA2-Enterprise (802.1x)
Network Security SPI Firewall
Access Control
IP & MAC Binding
Application Layer Gateway
Guest Network 1× 5 GHz Guest Network
1× 2.4 GHz Guest Network

SOFTWARE
Protocols IPv4
IPv6
Parental Controls URL Filtering
Time Controls
WAN Types Dynamic IP
Static IP
PPPoE
PPTP
L2TP
Quality of Service QoS by Device
NAT Forwarding Virtual Server
Port Forwarding
Port Triggering
DMZ
UPnP
IPTV IGMP Proxy
IGMP Snooping
DHCP Address Reservation
DHCP Client List
Server
DDNS NO-IP
Comex
DynDNS
Management Tether App
Webpage
Check Web Emulator>

PHYSICAL
Dimensions (W×D×H) 9.1 × 5.7 × 1.4 in
(230 × 144 × 35 mm)
Package Contents Wi-Fi Router Archer C20
Power Adapter
RJ45 Ethernet Cable
Quick Installation Guide

OTHER
System Requirements Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Cable or DSL Modem (if needed)
Subscription with an internet service provider (for internet access)
Certifications FCC, CE, RoHS
Environment Operating Temperature: 0°C~40°C (32°F ~104°F)
Storage Temperature: -40°C~70°C (-40°F ~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing

TEST DATA
WiFi Transmission Power CE:
<20dBm(2.4GHz)
<23dBm(5GHz)
WiFi Reception Sensitivity 5GHz:
11a 54M: -76dBm; 11ac VHT20 MCS8: -71dBm;

11ac VHT40 MCS9: -66dBm; 11ac VHT80 MCS9:
-62dBm
2.4GHz:
11g 54M: -76dBm11n; HT20 MCS7: -73dBm;
11n HT40 MCS7: -71dBm